

## DECLARATION OF PERFORMANCE No 9/SZ/16

1. Unique identification code of the product-type: **LTX-8**
2. Intended use/es: **Nailed-in plastic anchor for fixing of external thermal insulation composite systems with rendering in concrete and masonry**
3. Manufacturer: **Klimas Sp. z o.o.  
ul. Wincentego Witosa 135/137  
Kuźnica Kiedrzyńska 42-233 Mykanów**
4. Authorised representative: **not applicable**
5. System/s of AVCP: **system 2+**
6. European Assessment Document: **ETAG 014 / 02.2011**  
European Technical Assessment: **ETA-16/0509 / 17.08.2016**  
Technical Assessment Body: **Deutsches Institut für Bautechnik - DIBT**  
Notified body/ies: **1488**
7. Declared performance/s:

Essential characteristic	Performance											
	Base material	Concrete C12/15	Concrete C20/25 - C50/60	Clay bricks MZ	Calcium silicate bricks KS	Calcium silicate hollow block KSL	Vertically perforated clay bricks HLZ	Vertically perforated clay bricks porotherm 25	Lightweight concrete blocks LAC	Autoclaved concrete blocks AAC2	Autoclaved concrete blocks AAC7	
Characteristic tension resistance	Nrk[kN]	0,5	0,75	0,75	0,75	0,75	0,6	0,4	0,6	0,75	0,9	
Edge distances and spacing	Min. allowable spacing = 100mm						Min. allowable edge distance = 100mm					
Displacement	N[kN]/δ[mm]	0,17/1,5	0,25/1,5	0,25/0,5	0,25/0,8	0,25/1,0	0,2/1,2	0,13/0,6	0,2/0,9	0,25/0,8	0,3/1,3	
Plate stiffness	[kN/mm]	0,5										
Point thermal transmittance	[W/K]	0,000* / 0,000**										

\*) surface mount; \*\*) immersed mount

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **not applicable**

*The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*


Signed for and on behalf of the manufacturer by:

Kuźnica Kiedrzyńska  
20.08.2016

[place]  
[date of issue]

DORADCA TECHNICZNY

mgr Inż. Adam Szczepanowski  
- 333 -



[name]  
[signature]